

vertical pivot lift



AutoGate

Gate Entry Systems



7306 Driver Road, Berlin Heights, OH 44814
800.944.4283 (GATE) ■ AutoGate.com

VERTICAL PIVOT GATES



FITS NEARLY 100% OF ALL SITE APPLICATIONS



DOUBLE CONTOUR



RAILROAD



CURB NOTCHED



DUAL GATES

FEATURES AND BENEFITS

- Faster than slide gates
- Saves valuable space
- Superior operation in snow
- Fits any terrain (curbs, slopes, etc.)
- Easy to maintain
- Built-in battery backup
- Green – no hydraulics

ACCESSORY OPTIONS

- Warning lights
- Sirens
- Access control
- Accessories
- Traffic lights
- Retroreflective tape
- Heat packages



THE AUTOGATE DIFFERENCE

- Experts in site design and spec work
- National dealer network
- Internal tech support
- Superior quality construction
- In-house CAD design and engineering support





SHIELD® CRASH BARRIERS

RATINGS: K4/M30 • K8/M40 • K12/M50



M50/K12 – ACTIVE BARRIER

EVERY CRASH BARRIER CAN STOP A VEHICLE, BUT MOST ARE ...

- Maintenance intensive
- Have more down-time than up-time
- Can shut down entry/exit lanes or make you vulnerable to forced vehicle entry when down
- Poor reliability
- Costly to repair and service

AUTOGATE IS THE SOLUTION ...

- Dependable operation and low maintenance
- Survivability – no need to re-excavate and replace
- Back in service with minimal disruption¹
- Both anti-ram and pedestrian control²

¹ With spare drop arm and repair parts on hand

² With full gate panel



M30/K4 – STANDARD



M30/K4 – SHALLOW

BASIC SPECIFICATIONS

VISIT OUR WEBSITE FOR FULL PRODUCT SPECIFICATIONS

VERTICAL PIVOT GATE

Model: VPG2490 UL 325 Listed. CSA C22.2 No. 247 Listed.

- Operator size 68"L x 53"H x 30"W
- Continuous duty cycle
- Built-in battery backup
- Cycle speed: 10-12 seconds
- Gate lengths: 10-25' (picket style 24' max, chain link 25' max, consult factory for other sizes)
- Gate height: 4-8' from pad (consult factory for sizes over 8'). Gates over 8' require special crating and freight arrangements.
- Wind bracing: Rated for 150 mph hurricane wind loading

SHIELD CRASH BARRIERS

OPERATOR

- Operator size: 68"L x 51"H x 39"W
- Cycle time: 12-14 seconds
- Continuous duty

**Gates can be fabricated to the Drop Arm (Anti-Personnel Advantage)*

**Drop Arm or Gate can be outfitted with LED lights or reflective tape*

Model: AG-M30 CB-SF (DOS K4/L3/ASTM-2656/M30-PI)

Foundation Depth: 20" (Shallow Foundation only)

Model: AG-M30 CB (DOS K4/L3/ASTM-2656/M30-PI)

(For both Standard and Shallow Foundation Systems)

Gate Lengths: Barrier Arm only – Up to 19' Clear Open

With Full Gate Panel – Up to 17' Clear Open

Gates over 8' tall may be limited on length and require special shipping & freight arrangements.

Model: AG-M40 CB (DOS K8/L3/ASTM-2656/M40-PI)

Model: AG-M50 CB (DOS K12/L3/ASTM-2656/M50-PI)

Gate Lengths: Barrier Arm only – Up to 17' Clear Open

With Full Gate Panel – Up to 15' Clear Open

Gates over 8' tall may be limited on length and require special shipping & freight arrangements.

AVAILABLE ON ALL AUTOGATE SYSTEMS

- Genesis® Control Board
- Heat packages including arctic conditions
- Paint: PPG Commercial Coating, 2 Part High Solids Polyurethane.
- Powder coating available
- Security Breach Protection
- Warranty: 5 year residential, 3 year commercial/industrial

www.AutoGate.com

